INCH-POUND MIL-PRF-49467A SUPPLEMENT 1 19 May 1997

## PERFORMANCE SPECIFICATION

## CAPACITOR, FIXED, CERAMIC, MULTILAYER, HIGH VOLTAGE (GENERAL PURPOSE), ESTABLISHED RELIABILITY, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-49467A, dated 19 May 1997.

## SPECIFICATION SHEETS

MIL-PRF-49467/1 - Capacitor, Ceramic, Multilayer, High Voltage, 1,000 V DC, Established Reliability, Style HVR01.

MIL-PRF-49467/2 - Capacitor, Ceramic, Multilayer, High Voltage, 2,000 V DC, Established Reliability, Style HVR02.

MIL-PRF-49467/3 - Capacitor, Ceramic, Multilayer, High Voltage, 3,000 V DC, Established Reliability, Style HVR03.

MIL-PRF-49467/4 - Capacitor, Ceramic, Multilayer, High Voltage, 4,000 V DC, Established Reliability, Style HVR04.

MIL-PRF-49467/5 - Capacitor, Ceramic, Multilayer, High Voltage, 5,000 V DC, Established Reliability, Style HVR05.

MIL-PRF-49467/7 - Capacitor, Ceramic, Multilayer, High Voltage, 600 V DC, Established Reliability, Style HVR07.

Preparing activity: Army - CR

Agent: DLA - CC

(Project 5910-1867-99)

AMSC N/A 1 of 1 DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5910